

Notified body No. 2913

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9<sup>th</sup> March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

**indoors and outdoors solid wood panelling and cladding for walls and ceilings**

(construction product)

**look to the certificate annex**

(product type and parameters)

produced by the manufacturer

**DARKSIDEWOOD UAB,**

Nemenčinės rd. 230A, LT-15165 Miškonys, Vilnius dist., Lithuania /

company code: 304467367

(name and address of the manufacturer, company code)

In the manufacturing plant

Taurijos str. 45, LT-13110 Linkos vlg., Mickūnai elder., Vilnius dist., Lithuania

(address of the manufacturing plant)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 14915:2014\***

under system 1 are applied and that the factory production control fulfils all the prescribed requirements set out above.

This certificate was first issued **2022-07-15** and will remain valid as long as the harmonised standard remains valid and the manufacturing conditions in the plant and the factory production control itself are not modified significantly.

Information about validation of the certificate can be acquired at Inspekta, UAB, Certification body.

Certificate issued 2024-01-29

Romas Skripka  
Managing Director



\* - this standard is adopted as Lithuanian national standard

Inspekta, UAB  
Ukmergės str. 283B  
06313 Vilnius  
Lithuania  
+370 5 258 62 19  
[www.inspekta.eu](http://www.inspekta.eu)  
[info@inspekta.eu](mailto:info@inspekta.eu)



LIETUVOS  
NACIONALINIS  
AKREDITACIJOS  
BIURAS

PRODUKTO CERTIFIKAVIMAS  
DIEGTIŲ TŪBŲ

№-LA192-03

Name of the product	Thickness	Species code according to EN 13556	Reaction to fire according to EN 13501-1	Formaldehyde content according to EN 717-1	Preservative class according to EN 355
Charred larch cladding DARKSIDEWOOD Carbon	≥ 19 mm	LADC	D-s2,d0	E1	3
Charred spruce cladding DARKSIDEWOOD Carbon	≥ 17 mm	PCAB	F	E1	4
Charred larch cladding finished with fire retardant Ultra	≥ 19 mm	LADC	B-s1,d0	E1	3
Charred brushed larch cladding finished with Woca Exterior Wood Oil	≥ 17 mm	LADC	D-s2,d0	E1	3
Charred brushed spruce cladding finished with Woca Exterior Wood Oil	≥ 15 mm	PCAB	F	E1	4
Charred brushed spruce cladding finished with fire retardant Ultra	≥ 17 mm	PCAB	D-s2,d0	E1	4
Charred brushed spruce cladding finished with fire retardant Ultra (extra)	≥ 17 mm	PCAB	B-s1,d0	E1	4
Charred double brushed larch cladding finished with Woca Exterior Wood Oil	≥ 17 mm	LADC	F	E1	3
Charred double brushed spruce cladding finished with Woca Exterior Wood Oil	≥ 15 mm	PCAB	F	E1	4
Charred larch cladding DARKSIDEWOOD Vintage	≥ 17 mm	LADC	F	E1	3
Charred spruce cladding DARKSIDEWOOD Vintage	≥ 15 mm	PCAB	F	E1	4

Romas Skripka  
Managing Director  
2024-01-29